

AHD-IR30X

High Speed Dome Camera Day&Night 30X CON IR 110MT



- Speed Dome di alta qualità
- Alta risoluzione HD 1.3MEGAPIXEL 960p
- Day & Night con zoom 30x E IR DA 110MT
- Multiprotocollo
- Uso interno / esterno
- Staffa per fissaggio a muro in dotazione
- Costruzione robusta ed affidabile

30X Optical Zoom 120M IR SONY 700TVL CCTV Speed Dome Security Camera

Image sensor : 1/3"SONY CMOS 1.3MP 960p

External circulation cooling, rapid heat dissipation, water/fog/dust proof

OSRAM infrared lamp, Stepper motor drive.

Infrared analysis technique, reduce the IR working time and make the IR life long.

Image sensor	1/3" SONY CMOS
Signal model	AHD PAL/NTSC
Efficient pixel	1.3MP HD Resolution 960p
Lens	f=3.2 -86.4mm
Optical zoom	30x
Minimum illumination	0Lux (IR on)
Shutter time	PAL : 1 /50-1/10000S; NTSC : 1 /60-1/12000S
S/N ratio	>50dB
IR lighting distance	120m
Day and night	ICR
IR control	Auto
IR life	30,000 hours
IR power consumption	Manual
IR Model	Auto/manual/timing/synch
Focus	Auto/manual/zoom
Backlight compensation	On/Off
White balance	Auto
Pan	360° continuous
Tilt	10° - 90°

Design and Specifications are subject to change without notice

Manual control speed	0.01°/s- 80°/s
Preset	256
Patrol	8 groups
Swing	4 groups
Programmable Swing scan function	500 pieces command per group, keep to 10 minutes
Protocol	PELCO-D, PELCO-P,RS485
OSD language	English, Chinese menu
Fan control	Auto/ manual
Alarm	2 way output, 1 way input
Supply voltage	DC12V (4A)
Power consumption	35W
Material	Aluminium shell
Waterproof Criterion	IP66
Operating temperature	-35°C - 65°C
Assembly parts	bracket(wall or ceiling),User manual, AC adapter, Screws
Package dimension	300(L) x 300(W) x 425(H)mm

Design and Specifications are subject to change without notice

Microvideo s.r.l.

Via dei Castani, sn – 64014 Martinsicuro (TE) Italia
 mvideo@microvideo.eu - www.microvideo.eu

Tel ++39 0861 762259 Fax ++39 0861 761740